



RoHS
COMPLIANT
2002/95/EG

Messi & Paoloni srl

Via G. Conti N°1 - 60131 Ancona - Italy
Tel. +39 071 2861527 Fax +39 071 2861736
Internet: www.messi.it e-mail info@messi.it



TYPE **RG 58 C/U**

CONSTRUCTION DATA

Inner Conductor	19 x	Ø mm	Sn 0,18	± 0,01 mm	→
Dielectric			PE		
Physical Expansion					→
Triple Layer		Ø mm	2,95	± 0,1 mm	→
Ext. Screen (tape)			0		→
Screening Percentage			0		
Number of Wires		Tot.	112		
Second Screen (Braid)			Sn		→
Screening Percentage			92,3	%	
External Sheath			PVC	BLACK	
External Diameter		Ø mm	5,0	± 0,2 mm	→



Minimum Bending Radius (one bend) Outer/Inner **50 / 25**

ELECTRICAL DATA

Characteristic Impedance Ohm ± 3		50 ± 3
Capacitance pF/m. ± 2		101
Velocity Ratio		66 %
Attenuation (at 20° C.)		
	MHz.	50 dB/100 m. 10,8
	MHz.	200 dB/100 m. 23,0
	MHz.	400 dB/100 m. 33,7
	MHz.	600 dB/100 m. 43,0
	MHz.	800 dB/100 m. 51,2
	MHz.	1000 dB/100 m. 58,3

Structural Return Loss between	30-300	MHz. dB	> 35
	300-600	MHz. dB	> 30
	600-900	MHz. dB	> 30

Screening efficiency	100-900	MHz. dB	> 55
----------------------	---------	---------	----------------

Inner conductor resistance Ohm/Km	37
Outer conductor resistance Ohm/Km	17
Sheath Spark Testing kV	4KV

STANDARD Packing Type & Metres	AR100
Other Packings Type & Metres	BP500
Connectors BNC crimp type	C.BNC.58 MC
Connectors BNC to solder	C.BNC.58 MS

Legend: (*) AR100 = 100m Arianna refills
BP500 = 500m drums