



Messi & Paoloni srl

Via G. Conti N°1 - 60131 Ancona - Italy
Tel. +39 071 2861527 Fax +39 071 2861736
Internet: www.messi.it e-mail info@messi.it



TYPE **SAT 723/S (Type 17 VATC)**

CONSTRUCTION DATA

Inner Conductor	1 x	Ø mm	Cu 1,10	± 0,01 mm	→
Dielectric			PEG		→
Physical Expansion					→
Triple Layer		Ø mm	4,80	± 0,1 mm	→
Ext. Screen (tape)			AL-POL-AL		→
Screening Percentage			100 %		→
Number of Wires		Tot.	48		→
Second Screen (Braid)			AL		→
Screening Percentage			35 %		→
External Sheath			PVC	WHITE	→
External Diameter		Ø mm	6,80	± 0,2 mm	→



Minimum Bending Radius (one bend) Outer/Inner **70/35**

ELECTRICAL DATA

Characteristic Impedance Ohm ± 3			75
Capacitance pF/m. ± 2			52
Velocity Ratio			85 %
Attenuation (at 20° C.)	MHz.	5 dB/100 m.	1,2
	MHz.	50 dB/100 m.	2,7
	MHz.	200 dB/100 m.	6,5
	MHz.	470 dB/100 m.	11,9
	MHz.	800 dB/100 m.	16,7
	MHz.	860 dB/100 m.	17,4
	MHz.	1000 dB/100 m.	19,0
	MHz.	1750 dB/100 m.	26,1
	MHz.	2050 dB/100 m.	28,7
	MHz.	2150 dB/100 m.	29,4
	MHz.	2400 dB/100 m.	31,3
	MHz.	3000 dB/100 m.	35,3
Structural Return Loss between	30-300 MHz.	dB	> 33
	300-600 MHz.	dB	> 30
	600-900 MHz.	dB	> 30
Screening efficiency	100-300 MHz.	dB	> 75
	300-600 MHz.	dB	> 75
	600-990 MHz.	dB	> 85
Inner conductor resistance Ohm/Km			18,4
Outer conductor resistance Ohm/Km			41
Sheath Spark Testing kV			4

STANDARD Packing Type & Metres **AR100**

Other Packings Type & Metres **BP250** **BP500**

Connectors 'F' Screw Type **EX 6-4,9/8.3**

Connectors 'F' Compression Type **C.TV.FM.7**

With reference to Norms	CEI 46/13 (Cable TV installations)	✓
	CEI 12/15 (Cables for centralised systems)	✓
	EN 50117 (Cable networks)	✓
	CEI 46/1 (Construction parameters of the cables)	✓

Legend: (*) AR100 = 100m ARIANNA refills
BP250 = 250m Plastic bobbin
BP500 = 500m Plastic bobbin